

LDPE BLOWN FILM

*"Plastik pembungkus berkualitas,
memiliki ketahanan yang lebih baik,
dapat diaplikasikan untuk berbagai
macam kebutuhan industri".*

LIST PRODUK


SHRINK FILM/ TUBE



SHRINK HOOD



LAMINATION FILM



STRETCH HOOD



PE SHEET/ TUBE



PE BAG INDUSTRI



GEOMEMBRANE FILM



GREENHOUSE FILM



PLASTIK MULSA



TRASH BAG



MECHANICAL PROPERTIES BLOWN FILM

	UNIT	SPEKIFIKASI	TESTING MODE
Shrinkage	%	MD 0 - 80	ASTM D2732
	%	TD 0 - 50	ASTM D2732
Tensile	Mpa	MD 20 - 28	ASTM D882
		TD 19 - 21	ASTM D882
Elongation	%	MD 500 - 600	ASTM D882
	%	TD 600 - 700	ASTM D882

BLOWN FILM MACHINE FACTS

- Multilayer Blown Film Machine
- Thickness range 25 - 250 μ m
- Finished roll diameter range 150 - 800 mm
- Width range 300 - 5000 mm
- Lay flat width capability up to 2500 m
- Paper core diameter 77 mm
- Gusset capability
- Perforated capability
- Corona treated
- Output 21 MT/ day

